



SAFETY DATA SHEET LORD 506 DEGASSED

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name LORD 506 DEGASSED

Product number 3003761

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses For industrial and professional use only. Two component acrylic adhesive. Resin.

1.3. Details of the supplier of the safety data sheet

Supplier LORD Germany GmbH
Ottostrasse 28
D-41836 Hückelhoven
Germany
TEL : +49 (0) 2433-5257-0
FAX: + 49 (0) 2433-5257-18
Questions concerning the content of the SDS: EuropeMSDS@lord.com
General requests: info.europe@lord.com

Manufacturer LORD CORPORATION
111 LORD DRIVE
CARY, NC 27511-7923
U.S.A.

Information Tel.: 001 814 868 0924

1.4. Emergency telephone number

Emergency telephone NON-TRANSPORTATION EMERGENCY TELEPHONE NO. (USA): 001 814 763 2345

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 2 - H225

Health hazards Acute Tox. 4 - H302 Skin Corr. 1A - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335

Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) C;R34. Xi;R37. R43. F;R11.

2.2. Label elements

LORD 506 DEGASSED**Pictogram****Signal word**

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
 H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P243 Take precautionary measures against static discharge.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P280 Wear protective clothing, gloves, eye and face protection.

Contains

METHYL METHACRYLATE, METHACRYLIC ACID, 1,1'-(p-Tolylimino)dipropen-2-ol

2.3. Other hazards

Due to missing data, not all ingredients could be reviewed on PBT and vPvB criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

METHYL METHACRYLATE		< 60%
CAS number: 80-62-6		EC number: 201-297-1
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	F;R11 R43 Xi;R37/38	
Skin Irrit. 2 - H315		
Skin Sens. 1 - H317		
STOT SE 3 - H335		
STOT SE 3 - H335		
METHACRYLIC ACID		< 10%
CAS number: 79-41-4		EC number: 201-204-4
Classification	Classification (67/548/EEC or 1999/45/EC)	
Acute Tox. 4 - H302	C;R35 Xn;R21/22	
Acute Tox. 3 - H311		
Acute Tox. 4 - H332		
Skin Corr. 1A - H314		
STOT SE 3 - H335		
STOT SE 3 - H335		
Eye Dam. 1 - H318		

LORD 506 DEGASSED

1,1'-(p-Tolylimino)dipropen-2-ol		< 3%
CAS number: 38668-48-3 EC number: 254-075-1		
Classification Acute Tox. 2 - H300 Eye Dam. 1 - H318 Aquatic Chronic 3 - H412	Classification (67/548/EEC or 1999/45/EC) T;R25. Xi;R41. R52/53.	
2-HYDROXYETHYL METHACRYLATE		<1%
CAS number: 868-77-9 EC number: 212-782-2		
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317	Classification (67/548/EEC or 1999/45/EC) R43 Xi;R36/38	
HYDROQUINONE		< 0.1%
CAS number: 123-31-9 EC number: 204-617-8 M factor (Acute) = 10 M factor (Chronic) = 1		
Classification Acute Tox. 4 - H302 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Muta. 2 - H341 Carc. 2 - H351 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC or 1999/45/EC) Carc. Cat. 3;R40 Muta. Cat. 3;R68 Xn;R22 Xi;R41 R43 N;R50	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Keep affected person away from heat, sparks and flames. Move affected person to fresh air at once. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention.
Inhalation	Move affected person to fresh air at once. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration. Get medical attention if any discomfort continues.
Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothing and rinse skin thoroughly with water. Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Get medical attention immediately. Continue to rinse for at least 15 minutes.

4.2. Most important symptoms and effects, both acute and delayed

LORD 506 DEGASSED

General information	Effects may be delayed. Keep affected person under observation.
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea. Irritation of nose, throat and airway.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting. Drowsiness, dizziness, disorientation, vertigo.
Skin contact	Allergic rash. Chemical burns.
Eye contact	May cause blurred vision and serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Effects may be delayed. Keep affected person under observation.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Foam. Dry chemicals, sand, dolomite etc. Carbon dioxide (CO ₂). Water spray, fog or mist.
-------------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m ³ . Oxides of carbon. Oxides of nitrogen. Refer to section 10 of this safety data sheet for more information on hazardous decomposition products.
-------------------------	--

5.3. Advice for firefighters

Protective actions during firefighting	Move containers from fire area if it can be done without risk. Containers close to fire should be removed or cooled with water. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Use non-sparking tools. Avoid contact with skin or inhalation of spillage, dust or vapour. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.
--------------------------------	---

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. For waste disposal, see Section 13.
------------------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

LORD 506 DEGASSED

Usage precautions

Static electricity and formation of sparks must be prevented. Keep away from heat, sparks and open flame. Use explosion proof electric equipment. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Persons susceptible to allergic reactions should not handle this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.

Storage class

Flammable liquid storage. LGK 3 (TRGS 510)

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

METHYL METHACRYLATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 208 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 416 mg/m³

METHACRYLIC ACID

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m³

Short-term exposure limit (15-minute): WEL 40 ppm 143 mg/m³

HYDROQUINONE

Long-term exposure limit (8-hour TWA): WEL 0.5 mg/m³

Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Use explosion-proof general and local exhaust ventilation.

Eye/face protection

Use approved safety glasses with side shields. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Neoprene. Nitrile rubber. Butyl rubber. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

LORD 506 DEGASSED

Hygiene measures	Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke. Contaminated clothing should be placed in a closed container for disposal or decontamination. Warn cleaning personnel of any hazardous properties of the product.
Respiratory protection	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Gas filter, type A2.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Paste.
Colour	White/off-white.
Odour	Acrylic
Odour threshold	Not available.
pH	Not available.
Melting point	Not available.
Flash point	12°C SCC (Setaflash closed cup).
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0.99 - 1.04 @ 20°C
Solubility(ies)	Insoluble in water.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	20,000 - 70,000 (Brookfield HBF, Spindle 3, 5 rpm) mPas @ 25°C
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information

Volatile organic compound	This product contains a maximum VOC content of < 1% . The VOC-value given was calculated according to the guidelines specified in Directive 1999/13/EC.
----------------------------------	---

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

LORD 506 DEGASSED

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Hazardous polymerisation will not occur under normal conditions.

10.4. Conditions to avoid

Conditions to avoid Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Amines. Strong acids. Alkalis - inorganic. Organic peroxides/hydroperoxides.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO₂). Oxides of the following substances: Nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 1,647.1493079

Acute toxicity - dermal

ATE dermal (mg/kg) 5,423.78019075

Acute toxicity - inhalation

ATE inhalation (dusts/mists mg/l) 16.23886285

General information The present product is a chemical preparation within the meaning of the REACH Regulation 1907/2006/EC. To avoid testing the product in animal experiments the evaluation is made based on toxicological data and content by weight of the individual ingredients according to 1999/45/EC or analogous evaluations of comparable products.

Inhalation Irritating to respiratory system.

Ingestion Causes burns. Harmful if swallowed.

Skin contact May cause sensitisation by skin contact. Causes burns.

Eye contact Risk of serious damage to eyes.

SECTION 12: Ecological Information

Ecotoxicity Do not empty into drains, soil or bodies of water. The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Acute toxicity - fish No data available.

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

LORD 506 DEGASSED

Partition coefficient Not available.

12.4. Mobility in soil

Mobility The product is insoluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment Due to missing data, not all ingredients could be reviewed on PBT and vPvB criteria.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be considered. Do not dump into any sewers, on the ground, or into any body of water. Not be to be disposed of together with household waste. Any disposal practice must be in compliance with all local and national laws and regulations. Handle and dispose contaminated packages in the same way as the product itself. Fully cured product residues are generally not regarded as hazardous waste.

Disposal methods The product as supplied should be disposed of as hazardous waste according to European Directive 91/689/EEC. Empty containers must not be punctured or incinerated because of the risk of an explosion.

Waste class The waste code number applies to actual wastes depending on its origin and not to substances or mixtures as placed on the market. Only the practical application of the user enables the proper allocation. Allocation of the waste code number according to the European Waste Catalogue (Commission Decision 2000/532/EC and 2001/118/EC) should be carried out in agreement with the regional waste disposal company and/or the supervisory authority.

SECTION 14: Transport information

General This product may be shipped as part of 2 component acrylic adhesive kits under UN 3269 POLYESTER RESIN KIT.

14.1. UN number

UN No. (ADR/RID) 1133

UN No. (IMDG) 1133

UN No. (ICAO) 1133

14.2. UN proper shipping name

Proper shipping name (ADR/RID) ADHESIVES

Proper shipping name (IMDG) ADHESIVES

Proper shipping name (ICAO) ADHESIVES

Proper shipping name (ADN) ADHESIVES

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID subsidiary risk

LORD 506 DEGASSED

ADR/RID label 3

IMDG class 3

IMDG subsidiary risk

ICAO class/division 3

ICAO subsidiary risk

Transport labels



14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ICAO packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-D

Emergency Action Code •3YE

Hazard Identification Number 33
(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (JO L 396 du 30.12.2006).
Dangerous Substances Directive 67/548/EEC.
Dangerous Preparations Directive 1999/45/EC.

Water hazard classification WGK 1 (VwVwS 17 May 1999 Annex 4)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

LORD 506 DEGASSED

Key literature references and sources for data	Dangerous Properties of Industrial Materials Report, N.Sax et.al. Safety Data Sheets, Misc. manufacturers.
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Issued by	EU Regulatory Compliance Specialist (Product Safety).
Revision date	28/05/2015
Revision	4
Supersedes date	01/08/2012
SDS number	13302
Risk phrases in full	R11 Highly flammable. R21/22 Harmful in contact with skin and if swallowed. R25 Toxic if swallowed. R34 Causes burns. R35 Causes severe burns. R36/38 Irritating to eyes and skin. R37 Irritating to respiratory system. R37/38 Irritating to respiratory system and skin. R41 Risk of serious damage to eyes. R43 May cause sensitisation by skin contact. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

LORD 506 DEGASSED

Hazard statements in full

H225 Highly flammable liquid and vapour.
H300 Fatal if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H225 Highly flammable liquid and vapour.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H300 Fatal if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.