



SAFETY DATA SHEET

LORD 403E

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name LORD 403E
Product number 3020483,3018833

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses For industrial and professional use only. Two component acrylic adhesive. Resin.

1.3. Details of the supplier of the safety data sheet

Supplier LORD Germany GmbH
Ottostrasse 28
D-41836 Hückelhoven
Germany
TEL : +49 (0) 2433-5257-0
FAX: + 49 (0) 2433-5257-18
Questions concerning the content of the SDS: EuropeMSDS@lord.com
General requests: info.europe@lord.com

Manufacturer LORD CORPORATION
111 LORD DRIVE
CARY, NC 27511-7923
U.S.A.

Information Tel.: 001 814 868 0924

MSDS@lord.com

1.4. Emergency telephone number

Emergency telephone NON-TRANSPORTATION EMERGENCY TELEPHONE NO. (USA): 001 814 763 2345

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 2 - H225
Health hazards Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 Skin Sens. 1 - H317 STOT SE 3 - H335
Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xi;R37/38,R41. R43. F;R11.

2.2. Label elements

LORD 403E**Pictogram****Signal word**

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
 H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P243 Take precautionary measures against static discharge.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P280 Wear protective clothing, gloves, eye and face protection.

Contains

METHYL METHACRYLATE, METHACRYLIC ACID, 1,1'-(p-Tolylimino)dipropan-2-ol

2.3. Other hazards

Due to missing data, not all ingredients could be reviewed on PBT and vPvB criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

METHYL METHACRYLATE	< 35%
----------------------------	-----------------

CAS number: 80-62-6

EC number: 201-297-1

Classification

Flam. Liq. 2 - H225
 Skin Irrit. 2 - H315
 Skin Sens. 1 - H317
 STOT SE 3 - H335
 STOT SE 3 - H335

Classification (67/548/EEC or 1999/45/EC)

F;R11 R43 Xi;R37/38

Cyclohexyl methacrylate**< 5%**

CAS number: 101-43-9

EC number: 202-943-5

Classification

Skin Irrit. 2 - H315
 Eye Irrit. 2 - H319
 STOT SE 3 - H335
 STOT SE 3 - H335

Classification (67/548/EEC or 1999/45/EC)

Xi;R36/37/38.

LORD 403E

METHACRYLIC ACID < 3%	
CAS number: 79-41-4	EC number: 201-204-4
Classification Acute Tox. 4 - H302 Acute Tox. 3 - H311 Acute Tox. 4 - H332 Skin Corr. 1A - H314 STOT SE 3 - H335 STOT SE 3 - H335 Eye Dam. 1 - H318	Classification (67/548/EEC or 1999/45/EC) C;R35 Xn;R21/22
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate < 3%	
CAS number: 52628-03-2	EC number: 258-053-2
Classification Skin Corr. 1A - H314 Eye Dam. 1 - H318	Classification (67/548/EEC or 1999/45/EC) C;R34.
1,4-Dimethylpiperazine < 3%	
CAS number: 106-58-1	EC number: 203-412-0
Classification Flam. Liq. 2 - H225 Met. Corr. 1 - H290 Skin Corr. 1B - H314 Eye Dam. 1 - H318	Classification (67/548/EEC or 1999/45/EC) C;R34. R10.
1,1'-(p-Tolylimino)dipropan-2-ol < 3%	
CAS number: 38668-48-3	EC number: 254-075-1
Classification Acute Tox. 2 - H300 Eye Dam. 1 - H318 Aquatic Chronic 3 - H412	Classification (67/548/EEC or 1999/45/EC) T;R25. Xi;R41. R52/53.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.
Inhalation	Move affected person to fresh air at once. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.

LORD 403E

Skin contact Remove contaminated clothing and rinse skin thoroughly with water. Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.

4.2. Most important symptoms and effects, both acute and delayed

General information Effects may be delayed. Keep affected person under observation.

Inhalation Irritation of nose, throat and airway. Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting. Drowsiness, dizziness, disorientation, vertigo.

Skin contact Allergic rash. Causes burns.

Eye contact Irritation of eyes and mucous membranes. May cause blurred vision and serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Effects may be delayed. Keep affected person under observation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam. Dry chemicals, sand, dolomite etc. Carbon dioxide (CO₂). Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Specific hazards Fire or high temperatures create: Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrous gases (NO_x). Refer to section 10 of this safety data sheet for more information on hazardous decomposition products. The product is highly flammable. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Closed containers may rupture when exposed to extreme heat.

5.3. Advice for firefighters

Protective actions during firefighting Move containers from fire area if it can be done without risk. Containers close to fire should be removed or cooled with water. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid contact with skin or inhalation of spillage, dust or vapour. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

LORD 403E

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Static electricity and formation of sparks must be prevented. Keep away from heat, sparks and open flame. Use explosion proof electric equipment. Avoid contact with skin and eyes. Avoid spilling. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Flammable liquid storage. LGK 3 (TRGS 510)

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

METHYL METHACRYLATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 208 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 416 mg/m³

METHACRYLIC ACID

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m³

Short-term exposure limit (15-minute): WEL 40 ppm 143 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Use explosion-proof general and local exhaust ventilation.

Eye/face protection

Use approved safety glasses with side shields. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Neoprene. Nitrile rubber. Butyl rubber. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

LORD 403E

Hygiene measures	Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke. Contaminated clothing should be placed in a closed container for disposal or decontamination. Warn cleaning personnel of any hazardous properties of the product.
Respiratory protection	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Wear a respirator fitted with the following cartridge: Organic vapour filter.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Paste.
Colour	Tan.
Odour	Acrylate
Odour threshold	Not available.
pH	Not available.
Melting point	Not available.
Initial boiling point and range	Not available.
Flash point	15°C SCC (Setaflash closed cup).
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	1.10 - 1.15 @ 20°C
Solubility(ies)	Insoluble in water.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	100000 - 200000 cP (Brookfield) @ 25°C
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information

Volatile organic compound	This product contains a maximum VOC content of < 1% . The VOC-value given was calculated according to the guidelines specified in Directive 1999/13/EC.
----------------------------------	---

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

LORD 403E

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Hazardous polymerisation will not occur under normal conditions.

10.4. Conditions to avoid

Conditions to avoid Avoid exposure to high temperatures or direct sunlight. Avoid freezing.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids. Strong alkalis.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances: Oxides of the following substances: Nitrogen. Carbon. Phosphorus. Traces of hydrogen cyanide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 1,525.49856907

Acute toxicity - dermal

ATE dermal (mg/kg) 20,071.31124554

Acute toxicity - inhalation

ATE inhalation (dusts/mists mg/l) 60.09374624

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. The present product is a chemical preparation within the meaning of the REACh Regulation 1907/2006/EC. To avoid testing the product in animal experiments the evaluation is made based on toxicological data and content by weight of the individual ingredients according to 1999/45/EC or analogous evaluations of comparable products.

Inhalation

Irritating to respiratory system.

Ingestion

Harmful if swallowed.

Skin contact

May cause sensitisation by skin contact. Causes burns.

Eye contact

Risk of serious damage to eyes.

SECTION 12: Ecological Information

Ecotoxicity

Do not empty into drains, soil or bodies of water. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Acute toxicity - fish No data available.

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

LORD 403E

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

12.4. Mobility in soil

Mobility The product is insoluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment Due to missing data, not all ingredients could be reviewed on PBT and vPvB criteria.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be considered. Do not dump into any sewers, on the ground, or into any body of water. Not be to be disposed of together with household waste. Any disposal practice must be in compliance with all local and national laws and regulations. Handle and dispose contaminated packages in the same way as the product itself. Fully cured product residues are generally not regarded as hazardous waste.

Disposal methods The product as supplied should be disposed of as hazardous waste according to European Directive 91/689/EEC.

Waste class The waste code number applies to actual wastes depending on its origin and not to substances or mixtures as placed on the market. Only the practical application of the user enables the proper allocation. Allocation of the waste code number according to the European Waste Catalogue (Commission Decision 2000/532/EC and 2001/118/EC) should be carried out in agreement with the regional waste disposal company and/or the supervisory authority.

SECTION 14: Transport information

General This product may be shipped as part of 2 component acrylic adhesive kits under UN 3269 POLYESTER RESIN KIT.

14.1. UN number

UN No. (ADR/RID) 1133

UN No. (IMDG) 1133

UN No. (ICAO) 1133

14.2. UN proper shipping name

Proper shipping name (ADR/RID) ADHESIVES

Proper shipping name (IMDG) ADHESIVES

Proper shipping name (ICAO) ADHESIVES

Proper shipping name (ADN) ADHESIVES

14.3. Transport hazard class(es)

ADR/RID class 3

LORD 403E**ADR/RID subsidiary risk**

ADR/RID label 3

IMDG class 3

IMDG subsidiary risk

ICAO class/division 3

ICAO subsidiary risk**Transport labels****14.4. Packing group**

ADR/RID packing group II

IMDG packing group II

ICAO packing group II

14.5. Environmental hazards**Environmentally hazardous substance/marine pollutant**

No.

14.6. Special precautions for user

EmS F-E, S-D

Emergency Action Code •3YE

Hazard Identification Number (ADR/RID) 33

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Dangerous Substances Directive 67/548/EEC.
Dangerous Preparations Directive 1999/45/EC.

Water hazard classification WGK 2 (VwVwS 17 May 1999 Annex 4)**15.2. Chemical safety assessment**

No chemical safety assessment has been carried out.

SECTION 16: Other information

LORD 403E

Key literature references and sources for data	Dangerous Properties of Industrial Materials Report, N.Sax et.al. The Merck Index, 11. edition, 1989. Safety Data Sheets, Misc. manufacturers. GESTIS-database on hazardous substances (www.dguv.de/bgia/gestis-database).
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Issued by	EU Regulatory Compliance Specialist (Product Safety).
Revision date	28/05/2015
Revision	5
Supersedes date	29/03/2012
SDS number	13373
Risk phrases in full	R10 Flammable. R11 Highly flammable. R21/22 Harmful in contact with skin and if swallowed. R25 Toxic if swallowed. R34 Causes burns. R35 Causes severe burns. R36/37/38 Irritating to eyes, respiratory system and skin. R37 Irritating to respiratory system. R37/38 Irritating to respiratory system and skin. R41 Risk of serious damage to eyes. R43 May cause sensitisation by skin contact. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Hazard statements in full	H225 Highly flammable liquid and vapour. H290 May be corrosive to metals. H300 Fatal if swallowed. H302 Harmful if swallowed. H311 Toxic in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.