NBS-MG PRO 3 Black

ALTACHEM DESIGN PATENT

10. DOUBLE DIAMETER BARREL,

PTFE COATING, SERIAL NUMBER

9. LONG NOZZLE

8. STAINLESS STEEL NEEDLE WITH PTFE COATING

7. STEEL TRIGGER

6. HIGH QUALITY GASKET

5. STANDARD ACCESSORY: 1 EXTENSION TIP 'PRO-TIP'

OR, OPTIONALLY:

MAGAZINE CONTAINING 2 PRO-TIPS INSIDE THE **HANDGRIP**

1. HIGH QUALITY BASKET: **ALBART** PTFE TECHNOLOGY

> 2. ELEGANT BODY DESIGN, PTFE COATING

> > 3. DOSING KNOB WITH PROTECTION AGAINST LOSS

4. ERGONOMIC **HANDGRIP**



NBS-MG PRO 3 USP OVERVIEW

1. BASKET ALBA: SPECIALLY DESIGNED GEOMETRY, COMPATIBLE WITH ALL AVAILABLE FOAM & CLEANER CAN STANDARDS

RT: ROUNDED THREAD: CAN MOUNTING WITH VERY LOW RESISTANCE. NO RISK OF CUTTING INTO PLASTIC RING

PTFE COATING: FOR AIR-TIGHT CONNECTION WITH FOAM CANS, ALLOWS EASY CLEANING AFTER USE

PTFE NON-RETURN BALL: AVOIDS POLLUTION OF THE NON-RETURN BALL

2. BODY NEWLY DESIGNED ELEGANT BODY

LIGHT THANKS TO THE USE OF ALUMINIUM, WITH SPECIALLY DESIGNED RIBS FOR HIGH STIFFNESS

FULL PTFE COATING

3. DOSING KNOB EASY ADJUSTMENT OF THE REQUIRED AMOUNT OF FOAM

PROTECTION AGAINST LOSS: A SMALL SCREW INSIDE THE KNOB OFFERS PROTECTION AGAINST ACCIDENTAL LOSS

4. HANDGRIP ERGONOMIC SHAPE DESIGNED FOR INTENSIVE USE

5. PRO-TIP PLASTIC EXTENSION TIP TO BE ATTACHED ON THE BARREL FRONT, TO EASILY REACH NARROW HOLES AND GAPS

THE GUN CAN OPTIONALLY BE EQUIPPED WITH A MAGAZINE CONTAINING 2 PRO-TIPS ALWAYS READILY AVAILABLE

INSIDE THE HANDGRIP

6. GASKET A GASKET CONSISTING OF 3 RINGS (1 X PTFE, 2 X RUBBER) GUARANTEES LONG-TERM AIRTIGHTNESS —

IF REQUIRED. THE TENSION CAN BE ADJUSTED BY TURNING THE HEXAGONAL SCREW

NBS STANDARD GUARANTEES ≥ 50.000 CYCLES

7. NEEDLE MADE OF STAINLESS STEEL AND COATED WITH A HIGH QUALITY PTFE LAYER TO MINIMALIZE THE RESISTANCE

WHEN MOVING THROUGH THE GASKET

8. TRIGGER MADE OF STEEL FOR VERY HIGH STRENGTH

9. NOZZLE LONG SMOOTH NOZZLE WITHOUT SHARP EDGES FOR EASY CLEANING

PERFECT FIT WITH THE NEEDLE TIP FOR 100% AIRTIGHTNESS

10. BARREL CONTAINS A LASER-PRINTED SERIAL NUMBER FOR TRACKING AND TRACING PURPOSES

DOUBLE DIAMETER: WIDE AT THE BODY END: ALLOWS **HIGH OUTPUT**

NARROW AT THE NOZZLE END: ALLOWS EASY REACHING OF NARROW HOLES AND GAPS

